

OCTAVA | OCTAVA DOUBLE



OCTAVA

| | |
|-----------------------------|---|
| Material | steel pipes \varnothing 28 mm / steel profiles 30 x 30 mm |
| Connection thread | 2 x G1/2" |
| Testing overpressure | 1,3 MPa |
| Max. operating overpressure | 1,0 MPa |
| Max. operating temperature | 110 °C |
| Number of profiles | 7, 10, 13 |

OCTAVA DOUBLE

| | |
|-----------------------------|---|
| Material | steel pipes \varnothing 28 mm / steel profiles 30 x 30 mm |
| Connection thread | 2 x G1/2" |
| Testing overpressure | 1,3 MPa |
| Max. operating overpressure | 1,0 MPa |
| Max. operating temperature | 110 °C |
| Number of profiles | 14, 20, 26 |



OCTAVA 1800 x 606

OCTAVA

| Type H/L [mm] | Depth B [mm] | Weight [kg] | Water capacity [l] | Temperature exponent [n] | Heating Output [W] | | | Recommended power input paint [W] | Recommended power input chrome [W] | Connection span [mm] |
|---------------|--------------|-------------|--------------------|--------------------------|--------------------|-------------|-------------|-----------------------------------|------------------------------------|----------------------|
| | | | | | 75/65/20 °C | 70/55/20 °C | 55/45/20 °C | | | |
| 1800/318 | 58 | 18,5 | 9,4 | 1,276 | 766 | 623 | 399 | - | - | mc 50 |
| 1800/462 | 58 | 26,0 | 13,5 | 1,283 | 1094 | 888 | 568 | - | - | mc 50 |
| 1800/606 | 58 | 34,0 | 17,5 | 1,262 | 1422 | 1158 | 746 | - | - | mc 50 |

OCTAVA DOUBLE

| Type H/L [mm] | Depth B1 [mm] | Weight [kg] | Water capacity [l] | Temperature exponent [n] | Heating Output [W] | | | Recommended power input paint [W] | Recommended power input chrome [W] | Connection span [mm] |
|---------------|---------------|-------------|--------------------|--------------------------|--------------------|-------------|-------------|-----------------------------------|------------------------------------|----------------------|
| | | | | | 75/65/20 °C | 70/55/20 °C | 55/45/20 °C | | | |
| 1800/318 | 86 | 36,0 | 18,6 | 1,250 | 1096 | 895 | 579 | - | - | mc 50 |
| 1800/462 | 86 | 51,3 | 26,5 | 1,250 | 1564 | 1276 | 826 | - | - | mc 50 |
| 1800/606 | 86 | 66,7 | 34,6 | 1,250 | 2030 | 1657 | 1072 | - | - | mc 50 |

Thermal power measuring follows in accordance with EN 442.

Accessories (page 48, 49 and 50) is not part of the radiator.

